

ESLINGAS DE CADENA

GRADO 80

DOBLE BRAZO O RAMAL

SPECTRUM 8 Tamaño de cadena de Alaecien		60°	45°	30°
(pulg.)	(mm)	BRAZO DOBLE		
7/32	6	1632.9KG	1360.7KG	1133.9KG
1/4 (9/32)	7	2766.9KG	2222.6KG	1587.5KG
5/16	8	3538KG	2902.9KG	2041.1KG
3/8	10	5579.1KG	4535.9KG	3220.5KG
1/2	13	9434.7KG	7711 KG	5443.1KG
5/8	16	141967.4KG	11611.9KG	8210KG
3/4	20	22226KG	18143.6KG	12836.6KG
7/8	22	26852.6KG	21953.8KG	15512.8KG
1	26	37466.7KG	30572.1KG	21636.3KG
1-1/4	32	56789.7KG	46357.1KG	32794.7KG



DOS




DOSL



DOG



DOF



ADOSL



ADOS

TIPO	DESCRIPCION
DOS	Eslinga de cadena con eslabón maestro y gancho de carga
DOSL	Eslinga de cadena con eslabón maestro y gancho tipo Shurlock
DOG	Eslinga de cadena con eslabón maestro y ganchos de traba
DOF	Eslinga de cadena doble con gancho de fundición
ADOSL	Eslinga de cadena doble con ganchos de carga y acortadores
ADOS	Eslinga de cadena doble con ganchos de cierre positivo y acortadores



NUNCA EXCEDA LAS CAPACIDADES DE CARGA
NORMA DE REFERENCIA ASME B30.9