

ESLINGAS DE CADENA

GRADO 100

TRIPLE Y CUADRUPLE BRAZO O RAMAL

Tamaño de cadena de Alaación		60°	45°	30°
				
(pulg.)	(mm)	BRAZO TRIPLE Y CUADRUPLE		
7/32	6	3764 KG	3084 KG	2177 KG
1/4 (9/32)	7	5080 KG	4127 KG	2902 KG
5/16	8	6713 KG	5488 KG	3855 KG
3/8	10	10387 KG	8482 KG	5987 KG
1/2	13	17690 KG	14424 KG	10205 KG
5/8	16	26625 KG	21727 KG	15376 KG
3/4	20	41594 KG	33974 KG	24017 KG
7/8	22	50303 KG	41095 KG	29029 KG
1	26	70352 KG	57424 KG	40619 KG
1-1/4	32	106548 KG	86953 KG	61507 KG



QOF



QOG



QOS



QOSL

TIPO	DESCRIPCION
QOF	Eslinga de una cadena con eslabón maestro y gancho de fundición
QOG	Eslinga de cadena con eslabón maestro y ganchos de traba
QOS	Eslinga de cadena con eslabón maestro y ganchos de carga
QOSL	Eslinga de cadena y eslabón maestro con ganchos tipo shur-lock



NUNCA EXCEDA LAS CAPACIDADES DE CARGA
NORMA DE REFERENCIA ASME B30.9