

CABLE DE ACERO GALVANIZADO

Construcción 7x19 – 6x26 con alma de acero

CONST.	DIÁM.	RUPT. EN TONS	PESO × MTS
7×7	1/16"	0.24	0.011
7×7	1/32"	0.46	0.024
7×7	1/8"	0.85	0.042
7×7	3/16"	1.85	0.092
7×19	1/8"	1.00	0.043
7×19	3/16"	2.10	0.097
7×19	1/4"	3.50	0.164
7×19	5/16"	4.90	0.260
7×19	3/8"	7.20	0.362
7×19	7/16"	6.59	0.520
7×19	1/2"	9.22	0.623
7×19	5/8"	14.14	1.070
6×25	3/4"	24.55	1.550
6×25	7/8"	36.10	2.110
6×25	1"	43.08	2.750
6×25	1-1/8"	55.48	2.750
6×25	1-1/4"	68.49	2.750



CABLE DE ACERO GALVANIZADO CON FORRO

Construccion 7x19 con alma de acero

CONST.	DIÁM.	RESIST. A LA RUPT.	PESO × MTS
7×7	1/16" A 3/32"	0.22	0.020
7×7	3/32" A 1/8"	0.42	0.033
7×7	1/8" A 3/16"	0.77	0.054
7×7	3/16" A 1/4"	1.68	0.109
7×19	1/8" A 3/16"	0.91	0.054
7×19	3/16" A 1/4"	1.91	0.109
7×19	1/4" A 5/16"	4.45	0.164
7×19	3/8" A 9/16"	6.53	0.480



CABLE DE ACERO GALVANIZADO TIPO RETENIDA ALTA RESISTENCIA

Construccion 1x7

CONST.	DIÁM.	RESIST. A LA RUPT.	PESO × MTS
1×7	1/8"	1.30	0.048
1×7	3/16"	2.85	0.109
1×7	1/4"	4.75	0.180
1×7	5/16"	8.00	0.310
1×7	3/8"	10.80	0.406
1×7	1/2"	18.80	0.770
1×7	5/8"	28.10	1.210

